

LAUR SILICONE

LAUR RVG-45 and 50 SILICONE RUBBER

STRIP BUILDABLE SILICONE

The Laur RVG-XX Series (roller value grade) are general purpose, economical roller compounds that offer good finished roll properties and good thermal stability. This series of materials provides film release and intermediate heat transfer properties. They normally are supplied in strip form, but it is possible to provide custom packaging to meet specific needs.

TYPICAL PROPERTIES

Material	RVG-45	RVG-50
Durometer, Shore A	45	50
Tensile, psi (MPa)	850 (5.9)	925 (6.4)
Elongation, %	550	450
Tear B, ppi (kN/m)	76 (13)	95 (17)
Compression Set 22 h @ 350 °F	7	6
Specific Gravity, g/cc	1.28	1.39
Standard Color	Red	Red

ALL SLABS MOLDED 10 MINUTES @ 340 °F

The properties listed above are typical values and are not intended to be used for writing specifications. For assistance in selecting a compound for a specific application, please contact our technical department.

SHELF LIFE

When stored below 90 °F, this series of materials has a shelf life of 3 months from date of sale.

RVG Series

Revision 06-16

LAUR SILICONE, INC.
4930 S. M-18, BEAVERTON, MICHIGAN 48612-9181

WWW.LAURSILICONE.COM

TELEPHONE 989-435-7400
FAX 989-435-7707

Si-Release® is a trademark owned by Laur Silicone, Inc., Beaverton, MI.